

Telehandler / Zoom Boom

Used Telehandler Phoenix - Telehandlers have numerous names including a teleporter, Cherry picker, telescopic handler or boom lift. This industrial equipment is commonly used in a variety of industries including agriculture. This machine functions similarly to a crane and a forklift with the ability to extend upward and forward. Many different attachments can be used at the end of the articulating boom to facilitate a wide number of jobs. Common attachments include pallet forks, a winch, a bucket or a muck grab. The pallet forks are the most popular telehandler attachment. Pallet forks enable the operator to move loads to and from a variety of locations that would otherwise be considered unreachable with a standard forklift. These machines enable cargo pallets to be unloaded and loaded from a trailer and placed on rooftops, racking or other high and hard to access locations. Often, high rooftop locations would need a crane although, telehandlers can accomplish these tasks much more efficiently. Of course, it isn't always affordable or practical to use secondary equipment or a crane to complete certain tasks. A bucket or bucket grab is the most popular telehandler attachment in the agricultural industry. Relocating items from hard to reach areas that cannot rely on a wheeled loader or a backhoe loader give telehandlers a significant advantage. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Using one machine to finish numerous jobs saves storage space, money and time. Telehandlers commonly work alongside a crane jib. Various attachments may be used including rotators, dirt buckets, grain buckets and power booms. The agricultural models can use three-point linkage and power take-off to make telehandlers multi-tasking. However, the main advantage of the telehandler is additionally its' largest limitation. The boom raises or extends with heavy loads, acting as a lever. Even with rear counterweights, this machine may become unstable from time to time; decreasing the lift capacity when the distance between the center of the load and the front of the wheels or the working radius increases. If the machine works as a single boom loader instead of using twin arms while carrying a large load, there is a chance that weakness can occur even in the most carefully designed units. For instance, a telehandler with a five thousand pound capacity may be capable of safely lifting as little as four hundred pounds fully extended with a low boom angle with a retracted boom. The same piece of equipment with a five thousand pound lift capacity and retracted boom may be capable as supporting up to ten thousand pounds once the boom is raised to seventy degrees. These machines are equipped with a load chart to help outline which tasks are safely possible. These charts take the boom height, angle and weight into account. Updated telehandler models have computers and sensors. The operator is warned and even cut off further control input once the limits of the telehandler are surpassed. The lifting capacity is enhanced by front stabilizers that maximize the lifting capacity from a stationary position. Another option is a stabilizing rotary joint between lower and upper frames, often referred to as a mobile crane that can additionally utilize a bucket. Compact telehandler models are available in a variety of different weights, reach, sizes and boom designs. Telehandlers fall into the compact category if the unit weighs in at 11,000 lbs. or less. A two-stage boom is a popular option for compact models whereas the three or four boom design is common for bigger machines. A low pivot boom ensures better operator visibility for transporting loads on compact units. There are narrower and smaller dimensions offered with the compact telehandler. Compact telehandlers have a reach capacity ranging between 13 to 20 feet with a lift capacity ranging from 5k to 7k pounds. These versatile machines make the compact telehandler extremely popular. This machine can be utilized for carrying tools or as a pick and place unit. Compact units are ideal for cramped locations. It is common for contractors to use this machine during framing and for residential jobs where there are height restrictions. These machines can facilitate internal building access. Compact telehandlers are commonly used in nurseries, landscaping, multi-story construction, building strip malls and garages, masonry, erecting steel and more. Farming and agri-business applications often rely on telehandlers to accomplish many tasks.

Telehandlers are made with two or four-wheel drive as well as crab steering. This machine can traverse longer distances with two-wheel drive at higher speeds to facilitate easy travel between worksites. The four-wheel drive models offer the ability to traverse more difficult terrain and provide a tighter turning radius. Crab steering increases overall maneuvering and enables the front and back wheels to move 45 degrees to the left or the right. Compact telehandlers have numerous cab environments to choose from. There is a rollover protective cage to enhance safety on less expensive models. Higher models come with a heater, a completely enclosed cab, defroster and windshield wiper. Compact units feature spacious cab accommodations to keep operators totally comfortable. Additional features such as cup holders, air conditioning, tilt steering, suspension seats and satellite radio are all options. Different high-flow auxiliary hydraulics and high-pressure hydraulics run the variety of attachments. The different attachments allow the machine to be capable of many options. All of these attachments enable the machine to conduct a variety of jobs. Compact units are more commonly utilized for ground engaging jobs. Adding a bucket attachment can make a compact telehandler transform into a mini excavator. There are popular attachments including brooms for sweeping, truss booms for extended reach, side-shifting and rotating fork carriages, heavy and light-duty buckets, augers for planting trees or digging holes and many items. Skid steer attachments are being made for versatility and other compact telehandler designs.