

Very Narrow Aisle Forklift

Used Very Narrow Aisle Forklift Phoenix - Warehousing needs greatly focus on space-saving techniques and layout to maximize expensive square footage and decrease travel time needed to get goods from the loading docks and from point A to point B. Very narrow aisle solutions allow for more space to be dedicated to the storage of goods because less space is required for aisle access. These warehouse configurations are often referred to as warehouse optimization. Warehouse Optimization Implementing very narrow aisle warehouse optimization is a huge benefit of warehouse optimization. One of the most important benefits is the increased storage space. Since very narrow forklift trucks have been designed to take up significantly less space, warehouse aisle widths can be reduced to half the width needed by traditional forklifts. Certain models of very narrow aisle forklifts can increase the square foot storage capabilities by delivering greater stacking heights. This means that costs are decreased because less warehouse space is necessary for the same amount of stock than if a standard aisle configuration were used. Square footage is costly in urban areas and any way to reduce warehousing costs can save a company money. When planned carefully and properly, it is possible to increase warehouse storage area by up to 80 percent by implementing a very narrow aisle width configuration. Very narrow aisle design facilitates greater product access and more rack faces. Reduced travel time for storing items and gathering products are some of the key benefits to this warehouse layout as more products are found in an accessible location. Very narrow aisle layouts and narrow aisle layouts are popular for warehouses. Narrow aisles are measured as those that use fewer than eleven feet of aisle width. These widths reduce even further to roughly 6.5 feet for very narrow aisles. Both of these aisle widths provide significantly increased storage opportunities. Using a forklift for order picking and stocking can be difficult in these aisle widths, especially when turning. These challenges are met by using very narrow forklifts to gain access and complete tasks. When selecting a forklift for a job application, it is essential to know the aisle dimensions. Having the right aisle dimensions will save money and time instead of purchasing the wrong forklift that won't be able to conquer the applications. Finally, it is critical that any utilities, posts or columns are taken into account before settling on a specific narrow aisle forklift design as these may affect access to aisles by some forklifts or prevent warehouse optimization.

Very Narrow Aisle Forklift Trucks Very narrow aisle forklift trucks are almost always powered electrically, usually by rechargeable battery. Stand-up riders are a popular design for very narrow aisle forklift trucks. The most commonly used types of very narrow aisle forklift trucks are: 1. Reach trucks 2. Order pickers; 3. End-control riders; and 4. Turret or swing-mast.

Reach Forklift Trucks Reach trucks were designed as a version of the rider stacker forklift but specially modified for use in narrow aisles. It got its name by its function of reaching its forks forward to get to a load. The two kinds of reach trucks the moving carriage and the moving mast. The moving carriage works by raising and lowering the carriage and the driver. The moving mast works by raising and lowering the forks along the mast, while the operator stays at ground level. Of the two kinds of reach trucks, the moving mast reach truck is the safer of the two varieties. These machines rely on a kind of jointed framework known as a pantograph system that enables the operator to place a load or reach the load without moving the machine.

Order Pickers Order pickers have been designed and developed specifically for use in picking orders from high, typically hard-to-reach racks. These machines are used for picking up lighter stock that can be moved by hand. They lift the operator up to reach the goods by identifying and choosing certain items to create an order.

End-Control Riders End-control riders are used to pick loads located at floor level and transport the load horizontally, rather than lift or lower loads from various heights.

Turret or Swing-Mast Forklift Swing-mast or turret very narrow aisle forklifts feature an articulating swivel mast that pivots. Pallets can be set on either the right or left side of the forklift due to the machine's ability to use its' swinging mast.

Guided Very Narrow Aisle Trucks Rail or wire can guide the very narrow aisle forklift trucks down the aisle securely. Because the forklift is guided, thereby reducing the

possibility of the forklift bumping racks while moving down the aisle, the aisles can be extremely narrow. In rail-guided models, sets of rails are placed into the floor on each side of the aisle. They run the length of the aisle and also curve around the aisles' edge. Wheel guides on the forklift slide into the floor rails to stop the machine from traveling out of bounds. The wire-guidance system requires that the wires be installed into the floor, along the center of the aisle. Narrow aisle forklifts rely on a wire-guide system to help it communicate with the floor wires. This allows the machine to be steered by the wires, stopping it from traveling outside of the specific location.

Work Site Considerations Certain essential considerations need to be dealt with before using a narrow aisle configuration. Because these very narrow aisle configurations include very tall racking systems, the condition of the floor and the construction of the racks must be done properly in order to avoid potentially disastrous outcomes. There are four main locations that need to be ideally prepared before any racking system can be installed. These areas need to be monitored continuously including fixing cracks in the floor, ensuring the racks are straight, a level floor and an appropriate load capacity of the floor.

Level Floor Due to the racking system height, any minor floor slope can gravely impact how plumb the racks are, particularly over time if loads are placed and removed repeatedly on the racks. The height of the racking system means that any minute floor slope can have a negative impact on how straight the racks are, especially over time when loads are continually removed and placed on the racks. Without this foundation of a level floor, the stability of the racks could be jeopardized.

Crack Repair Cracks in the floor ideally should be fixed once they are noticed to ensure everyone's safety. The level of the floor can become unstable with cracks when they are only 3/8 inches wide. They will need to be filled properly with material as hard as the rest of the floor.

Floor Load Capacity The floor should meet certain minimum requirements before considering a narrow aisle configuration. The floor should have three thousand psi concrete minimum and contain evenly distributed rebar at three to four inches under the surface. Extra reinforcements might be needed depending on the load requirements and the configuration.

Plumb Racks Of great importance is the proper installation of the racking system. If installed improperly, there is a great chance of rack failure. Every rack needs to be plumb to ensure a safe system and work environment. If necessary, rack shims should be used to ensure the racks are plumb within 1 inch at the 30 foot height of the racks. Dangerous racking failure can occur if the above steps are not taken. Employees can become hurt or killed in the event that racking failure occurs. Goods can be damaged along with forklifts and other equipment. Because of these reason, these measures are the most important part of implementing a narrow aisle configuration for warehousing optimization.