

## Scissor Lift

Used Scissor Lift Phoenix - The industrial equipment that utilizes crisscrossed steel linked arms is scissor lifts. This equipment is utilized to create an “X” patterned support in order to accomplish vertical lifting. Workers use a sizeable rectangle platform that is secured to the top of the lifting apparatus. There are secure support railings along the platform edge for extra safety and to keep the operator safe. The scissor lift showcases a low profile that is excellent for compact, hard surfaces including pavement and concrete. Scissor lifts can use an electric motor or a combustion engine to transport and lift the machine. The lift function operates on a vertical plane only. In order for the operator to transport the lift horizontally, they will have to reposition the lift itself. Rough terrain and regular lift models rely on the same lifting technology to maneuver the lifting components. The rough terrain units are designed for driving on gravel and uneven surfaces. Oversized all-terrain tires often accompany rough terrain models to provide higher ground clearance. These scissor lifts feature 4WD to get through muddy and difficult terrain. Lower lifting heights are offered due to the higher center of gravity. Scissor lifts can seem intimidating if you have not used one before. Even though images of scissor lifts moving with the wind are easy to imagine, know that they have been specifically designed to provide complete operator safety and you won’t even feel the unit moving as it ascends or while it is extended. Numerous safety tests need to be completed prior to being capable of being sold. It is natural to feel uncomfortable if you are new to this type of equipment. Safety precautions need to be maintained at all times. There are many different kinds of electric scissor lift models to choose from, depending on what you will be using it for. The model you will prefer will largely depend on the types of jobs you plan on completing. How high you need to travel and how heavy the loads you will be transporting are all key factors. Extreme heights can be attained by different models depending on your specific application. Smaller models are commonly used for interior applications including warehouses and freight or factory settings. There is no need to purchase the largest model on the market if you are not going to require the fullest capacity. Optional railings and platforms are available on electrical scissor lifts to provide maximum safety. These units are safe and reliable. If these machines did not follow strict safety rules and particular inspections, they would not be for sale across the globe. These machines help us facilitate tasks that would otherwise not be possible. These machines are situated in place before elevating vertically. The operator needs to move the unit into the correct position before engaging the lift. There are a variety of safety features incorporated into the design. It is essential to follow operational guidelines to maintain everyone’s safety. There is a safe basket workspace on scissor lifts to ensure lifting tasks are more secure as opposed to hanging off of scaffolding or a ladder. Most scissor lifts utilize internally mounted batteries located inside the base of the machine to provide power. Electric scissor lifts need to be charged regularly; especially after prolonged work shifts. Numerous operators charge their units throughout the day or replace batteries every 12 hours. To charge the scissor lift, the operator parks it close to an electrical outlet within a well-ventilated location. After the scissor lift is parked the emergency shut-off switch is activated for safety. The sizeable red button found inside of the basket or the lift located near the charger or control box is the emergency shut-off switch. Newer scissor lifts commonly have their battery charger on the right side of the unit. Older machines may feature a battery charger on the rear of the machine. The charger is plugged into the AC extension cord in an area that is well-ventilated and then the extension cord is plugged into an electrical outlet. It is essential that the electrical cord length on the battery charger is short to prevent being run over or damaged. If the extension cord came out of the battery charger storage location during operation, there is a great potential for extreme danger. Ideally, all of the lights on the charger should become illuminated after the scissor lift is plugged in. Once the unit is plugged in, the batteries automatically start to charge. Once the unit is charged, the battery lights will turn green and the charger will turn off. Older scissor lifts need to use a meter to show zero volts once they are completely charged and this charger also turns off

after completion. The machine is ready to tackle another shift once the batteries are fully charged. It is common for warehouses and businesses to have numerous batteries continually charging to keep the scissor lift operating 24 hours a day.